

Chase & Sons® C1017 Separator Tape

CONSTRUCTION Polyester Film

DESCRIPTION Chase & Sons® C1017 is an opaque polyester film intended for use as a bedding or binder tape.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.00200"	0.051 mm	ASTM D374
Weight	13.1 lb/csy	71.1 g/m ²	Measured
Yield	7.6 sy/lb 1.21 lbs/mft @ 1" width	14.0 m ² /kg 0.71 kg/km @ 10mm width	Calculated
Tensile Strength	20000 psi	138 MPa	Calculated
Break Strength	40 lbs/1" width	70 N/10mm width	ASTM D882
Elongation	100%	100%	ASTM D882
Density		1.40 g/cc	Calculated

GENERAL PROPERTIES

Color	Opaque white
Core	3" or 6" Paper
Standard Pad Put-up	3"x12, 15, 18" or 6"x18"
Traverse Pad Put-up	3"x12"x3, 6, 12"

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.