

Chase & Sons® C1021 Separator Tape

CONSTRUCTION Polypropylene Film

DESCRIPTION Chase & Sons® C1021 is a high tensile, high yield, foamed monoaxial polypropylene tape intended for use in a separator, binder, or bedding application.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.00500"	0.127 mm	ASTM D374
Weight	11.7 lb/csy	63.5 g/m ²	Measured
Yield	8.5 sy/lb 1.08 lbs/mft @ 1" width	15.7 m ² /kg 0.63 kg/km @ 10mm width	Calculated
Tensile Strength	15000 psi	104 MPa	Calculated
Break Strength	75 lbs/1" width	131 N/10mm width	ASTM D882
Elongation	25%	25%	ASTM D882
Density		0.50 g/cm ³	Calculated

GENERAL PROPERTIES

Color	Opaque white
Core	3" or 6" Paper
Standard Pad Put-up	3"x12, 15, 18" or 6"x18"
Traverse Pad Put-up	3"x12"x3, 6, 12"

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.