

Chase & Sons® C1029 Separator Tape

CONSTRUCTION Polyester Film

DESCRIPTION Chase & Sons® C1029 is a white opaque polyester film typically used as a binder, barrier, or insulation tape.

TECHNICAL DATA

| Property | US Customary | | Metric | | Test Method |
|---------------------|-----------------|-----------------|-------------------------|-------------------------|-------------|
| Thickness | 0.00075" | 0.00092" | 0.019 mm | 0.023 mm | ASTM D374 |
| Weight | 5.1 lbs/csy | 6.0 lbs/csy | 27.7 g/m ² | 32.6 g/m ² | Measured |
| Yield | 19.6 sy/lb | 16.7 sy/lb | 36.1 m ² /kg | 30.7 m ² /kg | Calculated |
| Break Strength | 19 lbs/1" width | 22 lbs/1" width | 33 N/10mm width | 38 N/10mm width | ASTM D882 |
| Elongation | 125 % | 100 % | 125 % | 100 % | ASTM D882 |
| Dielectric Strength | 4.0 kV | 5.0 kV | 4.0 kV | 5.0 kV | ASTM D149 |

GENERAL PROPERTIES

| | |
|----------------|----------------|
| Color | Opaque white |
| Heat Shrinkage | 1% - 3% MD |
| Core | 3" or 6" Paper |

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.