

## Chase & Sons® L1132 Shielding Tape

**CONSTRUCTION** 0.00100 Polyester Film  
0.00070 Copper Foil



**DESCRIPTION** Chase & Sons® L1132 is a laminate of polyester film and copper foil intended for use as a corrosion resistant shielding tape.

### TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.00170"	0.043 mm	ASTM D374
Weight	36.2 lb/csy	196.6 g/m <sup>2</sup>	Measured
Yield	2.8 sy/lb 3.35 lbs/mft @ 1" wide	5.1 m <sup>2</sup> /kg 1.97 kg/km @ 10mm wide	Calculated
Tensile Strength	20500 psi	141 MPa	Calculated
Break Strength	35 piw	61 N/cm	ASTM D882
Elongation	20%	20%	ASTM D882
Density	2.62 oz/cu in	4.56 g/cm <sup>3</sup>	Calculated

### GENERAL PROPERTIES

Color	Red
Core	3" or 6", Paper
Standard Pad Put-up	3"x12, 15, 18" or 6"x18"
Traverse Pad Put-up	3"x12"x3, 6, 12"

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.