

Chase & Sons® L962-100CB Service Entrance Tape

CONSTRUCTION Glass Scrim
Polyester Film

DESCRIPTION Chase & Sons® L962-100CB is a laminated tape composed of glass scrim bonded to polyester film with a fire retardant adhesive. It is primarily intended for use as a replacement for glass braid on SEU and SER Service Entrance Cable and can also be used as a bedding or binding tape.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.0055"	0.140 mm	ASTM D374
Weight	17.5 lb/csy	95.0 g/m ²	Measured
Yield	5.7 sy/lb 1.62 lbs/mft @ 1" wide	10.5 m ² /kg 0.95 kg/km @ 10mm width	Calculated
Tensile Strength	22500 psi	155 MPa	Calculated
Break Strength	125 lbs/1" width	219 N/10mm width	ASTM D882
Flammability	Self-extinguishing when taped in place (contains a non-flammable scrim)		

GENERAL PROPERTIES

Color	Black
Surface	Dry PET side; slight tack reverse
Thread Count	20 x 10 (10 x 10 visual)"
Standard Core	3" or 6" Paper

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.