

## Chase & Sons® L962-50P Service Entrance Tape

**CONSTRUCTION**      Glass Scrim  
Polypropylene Film

**DESCRIPTION**      Chase & Sons® L962-50P is a laminated tape composed of glass scrim bonded to polypropylene film with a fire retardant adhesive. It is primarily intended for use as a replacement for glass braid on SEU and SER Service Entrance Cable and can also be used as a bedding or binding tape.

### TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.004"	0.102 mm	ASTM D374
Weight	13 lb/csy	70.6 g/m <sup>2</sup>	Measured
Yield	7.7 sy/lb 1.20 lbs/mft @ 1" wide	14.2 m <sup>2</sup> /kg 0.71 kg/km @ 10mm width	Calculated
Tensile Strength	19000 psi	131 MPa	Calculated
Break Strength	75 lbs/1" width	131 N/10mm width	ASTM D882
Flammability	Self-extinguishing when taped in place (contains non-flammable scrim)		

### GENERAL PROPERTIES

Color	White
Surface	Dry BOPP side; slight tack reverse
Thread Count	20 x 10 (10 x 10 visual)"
Standard Core	3" or 6" Paper

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.