


Chase & Sons® LG1031 Shielding Tape

CONSTRUCTION 0.00100" (25μ) Polyester Film
0.00200" (51μ) Aluminum Foil



DESCRIPTION Chase & Sons® LG1031 is a laminate of polyester film and aluminum foil intended for use as a shielding tape.

TECHNICAL DATA

| Property | US Customary | Metric | Test Method |
|------------------|--------------------------------------|---------------------------------------------------|-------------|
| Thickness | 0.00300" | 0.076 mm | ASTM D374 |
| Weight | 31.8 lb/csy | 172.7 g/m ² | Measured |
| Yield | 3.1 sy/lb 2.94 lbs/mft @ 1" width | 5.8 m ² /kg 1.73 kg/km @ 10mm width | Calculated |
| Tensile Strength | 12500 psi | 86 MPa | Calculated |
| Break Strength | 37 lbs/1" width | 65 N/10mm width | ASTM D882 |
| Elongation | 20% | 20% | ASTM D882 |
| Density | | 2.27 g/cc | Calculated |

GENERAL PROPERTIES

| | |
|---------------------|--------------------------|
| Color | Blue |
| Standard Core | 3" or 6", Paper |
| Standard Pad Put-up | 3"x12, 15, 18" or 6"x18" |
| Traverse Pad Put-up | 3"x12"x3, 6, 12" |

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.