

Chase & Sons® LG1096 Shielding Tape

CONSTRUCTION 0.00048 Polyester Film
0.00035 Aluminum Foil



DESCRIPTION Chase & Sons® LG1096 is a laminate of polyester film and aluminum foil intended for use as a shielding tape.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.00090"	0.023 mm	ASTM D374
Weight	8.4 lb/csy	45.6 g/m ²	Measured
Yield	11.9 sy/lb 0.78 lbs/mft @1" wide	21.9 m ² /kg 0.46 kg/km @10mm wide	Calculated
Tensile Strength	14500 psi	100 MPa	Calculated
Break Strength	13 piw	23 N/cm	ASTM D882
Elongation	75%	75%	ASTM D882
Density	1.15 oz/cu in	2.00 g/cm ³	Calculated

GENERAL PROPERTIES

Color	Natural
Core	3" or 6", Paper
Standard Pad Put-up	3"x12, 15, 18" or 6"x18"
Traverse Pad Put-up	3"x12"x3, 6, 12"

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.