

Chase & Sons® LG1204 Shielding Tape

CONSTRUCTION 0.00035" (9μ) Aluminum Foil
0.00090" (23μ) Polypropylene Film
0.00035" (9μ) Aluminum Foil



DESCRIPTION Chase & Sons® LG1204 is a tri-laminate of polypropylene film and aluminum foils intended for use as a shielding tape.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.00170"	0.043 mm	ASTM D374
Weight	12.5 lb/csy	67.9 g/m ²	Measured
Yield	8.0 sy/lb 1.16 lbs/mft @ 1" width	14.7 m ² /kg 0.68 kg/km @ 10mm width	Calculated
Tensile Strength	15500 psi	107 MPa	Calculated
Break Strength	26 lbs/1" width	46 N/10mm width	ASTM D882
Elongation	60%	60%	ASTM D882
Density		1.57 g/cc	Calculated

GENERAL PROPERTIES

Color	Natural
Standard Core	3" or 6", Paper
Standard Pad Put-up	3"x12, 15, 18" or 6"x18"
Traverse Pad Put-up	3"x12"x3, 6, 12"

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.