

Chase & Sons® S203 Flame Barrier Binder Tape

CONSTRUCTION Glass Fabric
Silicone Coating

DESCRIPTION Chase & Sons® S203 is a glass fabric tape impregnated with a cured silicone coating designed for high temperature, high strength binding applications. S203 is flame retardant and exhibits self-extinguishing characteristics.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.0041 in	0.104 mm	ASTM D374
Weight	20 lb/csy	108.6 gm/m ²	Measured
Yield	5.0 sy/lb 1.85 lbs/mft @ 1" width	9.2 m ² /kg 1.09 kg/km @ 10mm width	Calculated
Break Strength	120 lbs/1" width	210 N/10mm width	Calculated
Tensile	29500 psi	204 MPa	ASTM D882
Limiting Oxygen Index (LOI)	37	37	ASTM D2863

GENERAL PROPERTIES

Color	Off-white
Surface	Dry, dust free
Standard Core	3" or 6" Paper

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.