

Chase & Sons® S259T Binder Tape

CONSTRUCTION Nylon Fabric
Neoprene Coating

DESCRIPTION Chase & Sons® S259T is a single-faced, cured Neoprene coated nylon fabric. Designed for binder applications where it is beneficial that the coating is only on one side of the tape.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.005 in	0.127 mm	ASTM D374
Weight	16 lb/csy	86.9 gm/m ²	Measured
Yield	6.3 sy/lb 1.48 lbs/mft @ 1" width	11.5 m ² /kg 0.87 kg/km @ 10mm width	Calculated
Tensile Strength	15000 psi	104 MPa	ASTM D882
Break Strength	75 lbs/1" width	131 N/10mm width	Calculated
Elongation	25%	25%	ASTM D882

GENERAL PROPERTIES

Color	Black, other colors available by special order
Surface	Dry, tack-free, dust free
Standard Core	3" or 6" Paper

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.