



Chase & Sons[®] S262 Binder Tape

| CONSTRUCTION | Cotton Blended Fabric |
|--------------|-----------------------|
| | SBR Coating |

DESCRIPTION Chase & Sons[®] S262 is a single-faced SBR impregnated cotton blended tape for use as a binder or identification tape.

TECHNICAL DATA

| Property | US Customary | Metric | Test Method |
|------------------|--------------------------------------|--------------------------------------|-------------|
| Thickness | 0.011 in | 0.279 mm | ASTM D374 |
| Weight | 35 lb/csy | 190.1 gm/m² | Measured |
| Yield | 2.9 sy/lb 3.24 lbs/mft @ 1" width | 5.3 m²/kg 1.90 kg/km @ 10mm width | Calculated |
| Tensile Strength | 4500 psi | 31 MPa | ASTM D882 |
| Break Strength | 50 lbs/1" width | 88 N/10mm width | Calculated |
| Elongation | 5% | 5% | ASTM D882 |

GENERAL PROPERTIES

| Color | Black, White, Yellow, Orange, Red, Green, Blue, or Brown |
|---------------|---|
| Surface | Vulcanized, dry, dust free on coated side; fabric reverse |
| Standard Core | 3" or 6" Paper |

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions. Chase Corporation 295 University Avenue Westwood, MA 02090

Phone: 800-323-4182 Fax: 781-332-0701 www.chasecorp.com

An ISO 9001:2008 REGISTERED COMPANY