

Chase & Sons® S441 Binder Tape

CONSTRUCTION Polyester Fabric
SBR Coating

DESCRIPTION Chase & Sons® S441 is a double-faced SBR coated polyester tape for use as a binder or identification tape.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.0085 in	0.216 mm	ASTM D374
Weight	37.5 lb/csy	203.6 gm/m ²	Measured
Yield	2.7 sy/lb 3.47 lbs/mft @ 1" width	4.9 m ² /kg 2.03 kg/km @ 10mm width	Calculated
Tensile Strength	13000 psi	90 MPa	ASTM D882
Break Strength	110 lbs/1" width	193 N/10mm width	Calculated
Elongation	20%	20%	ASTM D882

GENERAL PROPERTIES

Color	Black, White, Yellow, Orange, Red, Green, Blue, or Brown
Surface	Vulcanized, dry, dust free
Standard Core	3" or 6" Paper
Other	Moisture Absorption: 2% maximum Thermal Resistance: Short Term 300°F, Long Term 200°F

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.