

Chase & Sons® S469R Semi-Conductive Tape

CONSTRUCTION Nylon Fabric
Coating

DESCRIPTION Chase & Sons® S469R is a semi-conducting, high yield, vulcanized, printed nylon tape that has been treated to ensure clean stripping from most insulation compounds.

TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.006 in	0.152 mm	ASTM D374
Weight	47.6 lb/csy	258.5 gm/m ²	Measured
Yield	2.1 sy/lb 4.41 lbs/mft @ 1" width	3.9 m ² /kg 2.58 kg/km @ 10mm width	Calculated
Tensile Strength	11500 psi	79 MPa	Calculated
Break Strength	70 lbs/1" width	123 N/10mm width	ASTM D882
Elongation	40%	40%	ASTM D882
Surface Resistance	5000 Ω/sq max	5000 Ω/sq max	ASTM F1529

GENERAL PROPERTIES

Color/Print	Black/White "SEMI-CONDUCTING TAPE---REMOVE WHEN SPLICING OR TERMINATING"
Surface	Dry, dust free
Standard Core	3" or 6", Paper

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.