

PaperTyger® F3284 is a new patent-pending, film, foil, paper laminate that contains a security barrier to prevent RFID detection at 13.56MHz and in the 860-980MHz range.

F3284 is designed for fabrication into activation labels, card sleeves and badge holders.

F3284 meets FIPS 201 requirements. Testing by independent laboratories proves that F3284 provides effective shielding at various HF and UHF frequencies.

Property	Imperial	Metric	Test Method
Basis Weight*	35 #	135gsm	T-410
Yield	5229 in ² / lb	0.00741 sm/g	Calculated
Caliper	3.25 mils	82.5 µm	T-411
Tensile (MD)	45 lbf/in	7.7 kn/m	T-494
Smoothness	120 Sheffield Units	120 Sheffield Units	T-538
Opacity	100%	100%	T-425

*Writing & Printing basis: 17 x 22 – 500 sheets per ream (1298.6 ft²)

HOW IT WORKS: The unique configuration of DEFENDER™ provides effective shielding at 13.56MHz and 860-980MHz by limiting the flow of RF energy between the reader and the smart card or other RFID device. The conductive layer in DEFENDER™ creates a barrier which impedes communication between the reader and the card.

SHIELDING PERFORMANCE: DEFENDER™ RFID Shield has been tested for shielding effectiveness at 13.56MHz by independent laboratories^{1, 2} using IEEE Method 299. This test involves the use of a test chamber fitted with a bulkhead opening where the shielding material to be tested is installed. This opening provides the only exit from the chamber for the RF signal. An RF generator is placed on one side of the bulkhead and a receiving antenna is placed on the other side. An RF signal of a known value is generated inside the chamber and measurements are taken by the receiving antenna outside the chamber. Shielding Effectiveness is the difference, expressed in decibels (dB), between the RF signal strength measured with the chamber opening empty and the signal measured when DEFENDER™ is installed. The shielding effectiveness results are contained in Tables 1 and 2.



PRODUCT DATA SHEET

Reference No.

F3284

**Durable RFID
Shielding
Material
3 PLY**

135gsm

35#

DEFENDER™



RFID0112



USA Headquarters
295 University Avenue
Westwood, MA 02090, USA

T: 781-332-0700
F: 781-332-0701
www.chasecorp.com

European Headquarters
Guildford Place,
124a Guildford Street,
Chertsey, Surrey,
KT16 9AH, UK

T: 01932 561144
F: 01932 561177
www.papertyger.us.com



Table 1: Shielding Effectiveness of DEFENDER™ at 13.56 MHz
Property Result Method

Property	Result	Method
RF Attenuation @ 13.56MHz (dB)	47.2	IEEE 299
Internal Skim Test (13.56MHz RF Reader)	Pass	Chase TP#606

1. D.L.S Electronic Systems, 1250 Paterson Drive Wheeling IL, 60090

Table 2: Shielding Effectiveness of DEFENDER™ in UHF Range

Property	Result	Method
RF Attenuation @ 860 MHz (dB)	56	IEEE 299
RF Attenuation @ 870 MHz (dB)	58	IEEE 299
RF Attenuation @ 880 MHz (dB)	50	IEEE 299
RF Attenuation @ 890 MHz (dB)	61	IEEE 299
RF Attenuation @ 900 MHz (dB)	52	IEEE 299
RF Attenuation @ 910 MHz (dB)	57	IEEE 299
RF Attenuation @ 920 MHz (dB)	51	IEEE 299
RF Attenuation @ 930 MHz (dB)	58	IEEE 299
RF Attenuation @ 940 MHz (dB)	52	IEEE 299
RF Attenuation @ 950 MHz (dB)	60	IEEE 299
RF Attenuation @ 956 MHz (dB)	54	IEEE 299
RF Attenuation @ 960 MHz (dB)	67	IEEE 299
RF Attenuation @ 970 MHz (dB)	56	IEEE 299
RF Attenuation @ 980 MHz (dB)	69	IEEE 299

1. D.L.S Electronic Systems, 1250 Paterson Drive Wheeling IL, 60090

No product can guarantee the protection of personal information or that identity theft won't occur. However, when used properly, the company's testing procedures indicate that DEFENDER™ can greatly reduce the opportunity for loss of valuable information.

Exclusive warranty: The Seller warrants for a period of 6 months from time of delivery its product to be free from defects in material and workmanship under normal wear and tear conditions. Seller warrants DEFENDER™ will provide RF shielding as defined by DEFENDER™ Technical Data Sheet for a period of 2 years assuming inner shielding layer is not compromised. Seller's obligation under this warranty is limited to replacement or, at its option, reimbursement of the purchase price of the product, provided that Buyer demonstrates to Seller's reasonable satisfaction within 60 days of shipment that the product is defective. Except as provided in this paragraph, Seller does not make and shall not be bound by any other warranty expressed, implied or otherwise. UNDER NO CIRCUMSTANCES WILL SELLER BE LIABLE FOR ANY LOSS, DAMAGE, EXPENSE OR INCIDENTAL OR CONSEQUENTIAL DAMAGE OF ANY KIND ARISING IN CONNECTION WITH THE USE OR INABILITY TO USE ITS PRODUCT.

**PRODUCT
DATA SHEET**

Reference No.

F3284

**Durable RFID
Shielding
Material
3 PLY**

135gsm

35#

DEFENDER™



RFID0112



USA Headquarters
295 University Avenue
Westwood, MA 02090, USA

T: 781-332-0700
F: 781-332-0701
www.chasecorp.com

European Headquarters
Guildford Place,
124a Guildford Street,
Chertsey, Surrey,
KT16 9AH, UK

T: 01932 561144
F: 01932 561177
www.papertyger.us.com

