

We make a material difference

SAFETY DATA SHEET

1. Identification

Product identifier Dualite E130-055D

Other means of identification

Product code ME005-1031

Filler Recommended use

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

Category 1

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Chase Corporation Specialty Chemical Intermediates

Address 9 Furman Hall Court

Greenville, SC 29609

United States

Telephone General Assitance 1-800-323-4182

Not available. E-mail

Chemtrec (US - 24 hrs) **Emergency phone number** 800-424-9300

> Chemtrec (Int'l - 24 hrs) 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

exposure

Not classified. **Environmental hazards**

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective

clothing/eye protection/face protection.

If exposed or concerned: Get medical advice/attention. Response

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Dualite E130-055D SDS US Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

99.08% of the mixture consists of component(s) of unknown acute oral toxicity. 99.08% of the mixture consists of component(s) of unknown acute dermal toxicity. 99.08% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 99.08% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Limestone		1317-65-3	80 - < 90
Isobutane		75-28-5	1 - < 3
1,1-dichloroethylene		75-35-4	< 0.2
Quartz (SiO2)		14808-60-7	< 0.2
Other components below reportable levels			10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantCoughing. Prolonged exposure may cause chronic effects.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Material name: Dualite E130-055D SDS US

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
Quartz (SiO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.	
US. OSHA Table Z-3 (29 CF	· · · · · · · · · · · · · · · · · · ·			
Components	Туре	Value	Form	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.	
		2.4 mppcf	Respirable.	
US. ACGIH Threshold Limit	Values			
Components	Туре	Value	Form	
1,1-dichloroethylene (CAS 75-35-4)	TWA	5 ppm		
Isobutane (CAS 75-28-5)	STEL	1000 ppm		
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
US. NIOSH: Pocket Guide to	o Chemical Hazards			
Components	Туре	Value	Form	
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3		
		800 ppm		
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	
logical limit values	No biological exposure limits noted for the	ingredient(s).		
osure guidelines	Occupational exposure to nuisance dust (t should be monitored and controlled.	otal and respirable) and re	spirable crystalline silica	
propriate engineering trols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.			
vidual protection measures, Eye/face protection	such as personal protective equipment Wear safety glasses with side shields (or g	goggles).		
Skin protection Hand protection	Wear appropriate chemical resistant glove	S.		
Other	Use of an impervious apron is recommend			
Respiratory protection	Use a particulate filter respirator for particulate		ding the Occupational	
respiratory protection	Exposure Limit.	nate concentrations excee	uing the Occupational	

Material name: Dualite E130-055D SDS US Thermal hazards Not applicable.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. **Physical state** Powder. **Form** Off-white Color Characteristic. Odor **Odor threshold** Not available. Not available. Ηq Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Slower than diethyl ether

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

- iowei

Not available.

Not available.

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Heavier Than Air

Relative density Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density0.11 - 0.15 g/cm³Explosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

VOC 13 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Acids. Fluorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: Dualite E130-055D

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Coughing.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

1,1-dichloroethylene (CAS 75-35-4)

Acute Oral

LD50 Rat 80 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory

occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,1-dichloroethylene (CAS 75-35-4) 2B Possibly carcinogenic to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated

exposure. Prolonged exposure may cause chronic effects.

Material name: Dualite E130-055D

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species **Test Results**

Dualite E130-055D

Aquatic

Fish LC50 Fish 95480.1016 mg/l, 96 hours estimated

Test Results Components Species

1,1-dichloroethylene (CAS 75-35-4)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 57 - 91 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2.13 1,1-dichloroethylene Isobutane 2.76

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D029: Waste 1,1-Dichloroethylene

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,1-dichloroethylene (CAS 75-35-4) Listed. Isobutane (CAS 75-28-5) Listed.

SARA 304 Emergency release notification

Not regulated.

Material name: Dualite E130-055D 6/8

ME005-1031 Version #: 07 Revision date: 02-21-2020 Issue date: 05-31-2015

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Carcinogenicity

categories Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,1-dichloroethylene (CAS 75-35-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-dichloroethylene (CAS 75-35-4)

Isobutane (CAS 75-28-5)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Quartz (SiO2), which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

 1,1-dichloroethylene (CAS 75-35-4)
 Listed: December 29, 2017

 Acrylonitrile (CAS 107-13-1)
 Listed: July 1, 1987

 Quartz (SiO2) (CAS 14808-60-7)
 Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,1-dichloroethylene (CAS 75-35-4)

Isobutane (CAS 75-28-5)

Quartz (SiO2) (CAS 14808-60-7)

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

United States & Puerto Rico

Material name: Dualite E130-055D

Yes

On inventory (yes/no)*

16. Other information, including date of preparation or last revision

 Issue date
 05-31-2015

 Revision date
 02-21-2020

Version # 07

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 0

Flammability: 0 Instability: 0

Disclaimer The information offered in this data sheet is designed only as guidance for the safe use, storage

and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only.

No warranty, expressed or implied is made.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: Dualite E130-055D SDS US